

POLE SIZE	ARM SIZE	ANCHOR BOLTS	BASE PLATE	BOLT CIRCLE
(WALL THICKNESS X O.D. AT BASE OF PLATE X O.D. AT POLE TOP X POLE HEIGHT)	(FLANGE PLATE SHALL ACCEPT ANY MAST ARM LISTED WITH THE FOLLOWING INCLUSIVE LENGTHS) (SEE NOTE 2)	(ALL BOLTS SHALL HAVE A CLASS OF FIT RATING OF 2A/2B UNC)	(SIDE × SIDE × PLATE THICKNESS)	(DIA.)
7 GAUGE x 12" x 8.22" x 27'-0"	38′	FOUR (4)- 1½" DIA. x 54" LENGTH SIX (6) THREADS PER IN.	17" x 17" x 1 ¹ 2"	16"
3 GAUGE x 13" x 9.22" x 27'-0"	50′	FOUR (4)- 1 ³ / ₄ " DIA. x 66" LENGTH FIVE (5) THREADS PER IN.	181 ₂ " x 181 ₂ " x 2"	18"
O GAUGE x 15" x 11.22" x 27'-0"	60′ & 70′	FOUR (4)- 2" DIA. x 72" LENGTH 4½ THREADS PER IN.	23" × 23" × 2"	22"

NOTES:

- 1. ALL ANCHOR BOLT HOLE DIAMETERS SHALL BE 38" LARGER THAN THE ANCHOR BOLT DIAMETER LISTED.
- 2. REFER TO APPROPRIATE 800 SERIES STANDARD PLATE FOR FLANGE PLATE AND ACCESS HOLE DETAILS.
- 3. REFER TO APPROPRIATE 800 SERIES STANDARD PLATE FOR BOLT CIRCLE AND ANCHOR BOLT PLACEMENT.

